






- Shockproof dial indicatorMade of stainless steel

1312-150A

Dial indicator graduation: 0.02mm									(mm)	
Code	Range	Accuracy	Thumb roller	L	а	b	С	d	D	t
1312-150A*	0-150mm	±0.03mm	with	235	21	16.5	16	40	Ø39	6.5
1312-200A*	0-200mm	±0.03mm	with	288	24	19	16	48	Ø39	6.5
1312-300A*	0-300mm	±0.03mm	with	410	28	22	20	62	Ø44.5	7.5
1312-100AW *	0-100mm	±0.02mm	without	165	18	13	13	30	Ø32	6



Dial	indicator	graduation:	0.01mm
------	-----------	-------------	--------

Dial Indicator graduation: 0.0 mm (n								(mm)		
Code	Range	Accuracy	Thumb roller	L	а	b	С	d	D	t
1311-150A*	0-150mm	±0.03mm	with	235	21	16.5	16	40	Ø39	6.5
1311-200A*	0-200mm	±0.03mm	with	288	24	19	16	48	Ø39	6.5
1311-300A*	0-300mm	±0.03mm	with	410	28	22	20	62	Ø44.5	7.5

^{*}Supplied with manufacturer inspection certificate

DIAL CALIPERS WITH CARBIDE TIPPED JAWS






- Shockproof dial indicator
- Dial indicator graduation: 0.02mm
- Carbide tipped jaws for inside and outside measurements
- Made of stainless steel



(mm)
-----	---

Code	Range	Accuracy	L	а	b	C	d	D	t
1339-150*	0-150mm	±0.03mm	235	21	16.5	16	40	Ø39	6.5
1339-200*	0-200mm	±0.03mm	288	24	19	16	48	Ø39	6.5
1339-300*	0-300mm	±0.03mm	410	28	22	20	62	Ø44.5	7.5

^{*}Supplied with manufacturer inspection certificate



DIAL CALIPERS



- Shockproof dial indicator
- Dial indicator graduation: 0.02mm
- Made of stainless steel

							(mm)
Code	Range	Accuracy	а	С	d	е	L
1316-500	0-500mm	±0.05mm	18	21	90	20	650
1316-600	0-600mm	±0.05mm	18	21	90	20	750
1316-1000	0-1000mm	±0.07mm	24	28	150	20	1190
1316-1500	0-1500mm	±0.11mm	24	28	150	20	1690

