
15






WIRELESS DIGITAL MEASURING TAPES + LASER DISTANCE METERS







- Built-in bluetooth or wireless Zigbee transmission
- Display with backlight
 Automatic power off: laser 30s, main unit 180s
 Can work continuously for 5 hours
 Can store 50 groups of measurement data





SPECIFICATION

Code		9563-C40	9563-C60	9563-WL40	9563-WL60		
Output		bluetooth (data can be transmitted to APP) wireless Zigbee (optional receiver needed: code 7315-2/3/6/7 (data can be transmitted to excel, word, txt et					
	range	5m					
Digital	resolution	0.001m					
measuring	accuracy	±1.5mm	±1.5mm				
tape	blade width	19mm					
	horizontal stand-out	≥1.8m					
	range	40m	60m	40m	60m		
	resolution	0.001m					
Laser distance	accuracy	±(3+D/20)mm, D: me	easured distance, unit	: m			
meter	units	m, ft, in, ft+in					
	laser type	630~670nm, <1mW,	class 2				
	measurement function	single, continuous, a	rea, volume, pythagor	ras measurement			
Operation te	mperature	0~40°C					
Storage tem	perature	-10~60°C					
Power supp	y	built-in rechargeable lithium battery					
Dimension (L×W×H)	95×74×56mm					
Weight		313g					



MEASURING TAPES










■ Non-glare nylon surface for wear resistance

 Accuracy: ±(0.3+0.2L)mm (L is the measured length rounded up to the next whole meter), meet MI-008 of DIRECTIVE 2014/32/EU



Individual (1 pc per package)

Code	Range	Graduation	Width of tape A	W	Н
7140-3	0-3m	1mm	16mm	28mm	62mm
7140-5	0-5m	1mm	19mm	30mm	68mm
7140-8	0-8m	1mm	25mm	38mm	78mm

Set (12 pcs per package)

7140-5

٠.		0 /			
Code	Range	Graduation	Width of tape A	W	н
7140-3A	0-3m	1mm	16mm	28mm	62mm
7140-5A	0-5m	1mm	19mm	30mm	68mm
7140-8A	0-8m	1mm	25mm	38mm	78mm

MEASURING TAPES (ECONOMIC TYPE)





■ Non-glare nylon surface for wear resistance

 Accuracy: ±(0.3+0.2L)mm (L is the measured length rounded up to the next whole meter), meet MI-008 of DIRECTIVE 2014/32/EU




7147-5S

Individual

Code	Range	Graduation	Width of tape
7147-5	0-5m	1mm	19mm





Set

15

Code	Range	Graduation	Width of tape	Remark
7147-5S	0-5m	1mm	19mm	include 12pcs 7147-5

MEASURING TAPES

- Non-glare nylon coating tape, wear resistance
- Accuracy: ±(0.3+0.2L)mm
 (L is the measured length
 rounded up to the next whole meter),
 meet MI-008 of DIRECTIVE 2014/32/EU






Individual (1 pc per package)

Code	Range	Graduation	Width of tape A	W	н
7142-5	0-5m/0-16ft	1mm, 1/16"	19mm	31mm	64mm

Set (12 pcs per package)

Code	Range	Graduation	Width of tape A	W	Н
7142-5A	0-5m/0-16ft	1mm, 1/16"	19mm	31mm	64mm





MEASURING TAPES (ECONOMIC TYPE)





- Matte coating
- Accuracy: ±(0.3+0.2L)mm (L is the measured length rounded up to the next whole meter), meet MI-008 of DIRECTIVE 2014/32/EU

Individual

Code	Range	Graduation	Width of tape
7148-5	0-5m	1mm	25mm




Unit: mm 35 locking knob

Set

Code	Range	Graduation	Width of tape	Remark
7148-5S	0-5m	1mm	25mm	include 12pcs 7148-5


EG II

MEASURING TAPES



 Accuracy: ±(0.3+0.2L)mm (L is the measured length rounded up to the next whole meter), meet MI-008 of DIRECTIVE 2014/32/EU








SELF ADHESIVE MEASURING ROLLS

type of reading








Self adhesive back

■ Steel tape, non-glare coating, wear resistance


7139-50

Code	Range (L)	Graduation	Accuracy	Type of reading
7139-50	50-0-50cm	1mm	±0.2mm	middle to both sides
7139-100	0-100cm	1mm	±0.4mm	left to right




LONG MEASURING TAPE

graduation




- High tensile strength fibreglass tape
- Nylon coating tape, wear resistance
- Accuracy: ±(0.3+0.2L)mm (L is the measured length rounded up to the next whole meter), meet MI-008 of DIRECTIVE 2014/32/EU






Code	Range	Graduation	Width of tape	W	Н
7143-50	0-50m/0-165ft	1mm, 1/8"	13mm	220mm	320mm


MEASURING WHEEL (BASIC TYPE)



■ Three-section adjustable handle







15





after folding


backpack (included)

- ABS plastic frame, wear-resistant PU tire
 Two-section foldable handle

Code	Range	Resolution
7145-1	0.1-9999.9m	0.1m



MEASURING WHEEL




IP40

- IP40 dust/waterproof
- Measuring length of curve
- Four measurement modes: length, rectangle area, diameter of circle, cube
- Resolution: 0.001m/0.01ft
- Button function: on/off, mm/inch, one or two sides set, measurement mode conversion, measurement
- Battery CR2032, automatic power off



7146-10



DIGITAL MEASURING WHEEL

scriber

Code	Range	Accuracy	
7146-10	0-10m/0-32.8ft	±0.3%L (L is the measured length)	

RIGID RULER

groove on the back



7113-300A

■ Rigid ruler

■ With groove on the back, suitable for combination square set (2278 series)

Satin chrome plated

Code	Range	Graduation		A	
		front	back	Accuracy	L
7113-300A	300mm/12"	0.5mm and 1/32"	1mm and 1/64"	±0.15mm	300mm

